

The Aluminium Spray Gun



Product Code: 6000

Material: High-strength aluminum-silicon alloy

Surface: Anodized corrosion resistant surface, particularly resistant to alkaline cleaners

Tip: Chromed brass tip with patent cone for secure fixing of the attachments.
O-Ring gasket bore 2.5mm

Spout: Chromed brass spout. Bore 4.0 mm, with M16 threaded holes for mounting the holding cone.
Usable with table mounting or wall bracket.
Possible to assemble by hand without using tools.

Handle: Thermo-insulating silicone grip. Temperature stability up to 200°C (392 °F)

Maximum pressure: 10 bar (145.04 psi)

Work pressure: 0 to 6 bar (00.00 – 87.02 psi)

Temperature range: -10°C (dry) to 60°C (14 – 140 °F)

Cleaning material: Water, compressed air, nitrogen, carbon dioxide

Mass: ca. 300g (approx. 0.66 lb)

Flow rate with air at 20 ° C and completely opened gun

bar	1	2	3	4	5	6	7	8	9	10
l/ min	60	90	125	180	220	250	280	340	360	390

Flow rate with water at 16 ° C and completely opened gun

bar	2	3	4	5	6	7	8
l/ min	3.2	4.8	6.5	7.1	7.8	9.1	12.8

Web: www.minervastericlean.co.uk
Email: info@minervastericlean.co.uk
Tel: +44 (0) 1249 820178